Claims

In a multicarrier communication system in which a signal to be transmitted comprises data bits to be converted into a symbol modulated by each subcarrier of the signal prior to transmission on a channel, a method for minimizing a peak to average power ratio while minimizing introduction of errors into the signal to be transmitted:

sampling the symbols to be transmitted of a frame;

compare magnitudes of the samples of the frame to a predetermined threshold to determine whether sample magnitudes in the frame violate the predetermined threshold, the predetermined threshold being selectable to control the number of samples violating the threshold;

responsive to determining a sample magnitude does violate the predetermined threshold, applying a differentiable penalty function to the samples having magnitudes exceeding the predetermined threshold;

computing a net penalty function value, the net penalty function value responsive to the individual penalty function values computed for the samples having magnitudes exceeding the predetermined threshold;

computing a gradient vector responsive to the net penalty function value;

determining a direction of the gradient vector;

determining an upper limit correction value for each symbol, the upper limit correction value being selectable to control an amount of signal to noise ratio deterioration;

applying a correction to the symbols to be transmitted in a direction opposite to the direction of the gradient vector of a magnitude not exceeding the determined correction values for each symbol; and

transmitting the corrected symbols to the channel.

2. The method of claim 1 wherein determining an upper limit correction value for each symbol, the upper limit correction value further comprises:

computing an interpoint distance between symbols;

selecting a correction value for a symbol as a value less than the interpoint distance to ensure that the symbol is not mistaken for other symbols.

3. The method of claim 1 wherein applying a differentiable penalty function to the samples having magnitudes exceeding the predetermined threshold comprises:

applying the function:

$$h(x[k]) = \begin{cases} (x[k]-T)^{2m} & if \quad x[k] \geq T \\ 0 & if \quad |x[k]| \leq T \\ (x[k]+T)^{2m} & if \quad x[k] \leq -T \end{cases}$$

where m is a positive integer that decides the severity of penalty, T is the predetermined threshold, x is the frame of data symbols expressed by: $X = (r_0, r_1 \exp(j\theta_1), r_2 \exp(j\theta_2), \ldots, r_{N/2-1} \exp(j\theta_{N/2-1}), r_{N/2})$, where r_i and θ_i denote the magnitude and phase of symbol in channel i, and k is the number of the symbol.

4. The method of claim 3 wherein the net penalty function comprises:

$$f(x) = \sum_{k=0}^{N-1} h(x[k])$$

5. The method of claim 4, wherein the gradient vector is computed as:

$$\frac{\partial f}{\partial r_i} = \sum_{k=0}^{N-1} \frac{dh(x[k])}{dx[k]} \cos\left(\frac{2\pi ki}{N} + \theta_i\right); i \in \{1,\ldots, N/2-1\}$$

$$\frac{\partial f}{\partial r_0} = \sum_{k=0}^{N-1} \frac{dh(x[k])}{dx[k]}; \frac{\partial f}{\partial r_{N/2}} = \sum_{k=0}^{N-1} \frac{dh(x[k])}{dx[k]} \cos(\pi k)$$

$$\frac{\partial f}{\partial \theta_i} = -r_i \sum_{k=0}^{N-1} \frac{dh(x[k])}{dx[k]} \sin\left(\frac{2\pi ki}{N} + \theta_i\right); i \in \{1,\ldots, N/2-1\}$$

6. The method of claim 1 wherein the gradient vector is computed only as a function of the magnitude of the sample values.

7. The method of claim 1 wherein computing a net penalty function value comprises adding together the individual penalty function values computed for the samples having magnitudes exceeding the predetermined threshold to generate the net penalty function value.

8. In a multicarrier communication system in which a signal to be transmitted comprises data bits to be converted into a symbol modulated by each subcarrier of the signal prior to transmission on a channel, for a signal having a single peak in a frame, a method for minimizing a peak to average power ratio while minimizing introduction of errors into the signal to be transmitted:

sampling the symbols to be transmitted of the frame;

compare magnitudes of the samples of the frame to a predetermined threshold to

determine whether sample magnitudes in the frame violate the

predetermined threshold, the predetermined threshold being selectable to control the number of samples violating the threshold;

determining an upper limit correction value for each symbol, the upper limit correction value being selectable to control an amount of signal to noise ratio deterioration;

computing a peak reduction kernel responsive to the upper limit correction values;

responsive to determining a sample magnitude does violate the predetermined threshold, applying the peak reduction kernel to the sample to reduce the peak of the frame; and

transmitting the modified symbol.

9. The method of claim 8 wherein computing a peak reduction kernel responsive to the upper limit correction values comprises:

determining a phase component and an amplitude component of the upper limit correction values; and

setting the phase component of the upper limit correction values to zero to ensure that the peak reduction kernel has its peak value at the first sample of the frame.

10. The method of claim 8 wherein applying the peak reduction kernel to the sample to reduce the peak of the sample comprises:

rotating the peak kernel by amount to ensure a peak of the peak reduction kernel coincides with a peak of the frame;

determining whether the peak of the kernel has a sign equal to a sign of the peak of the frame;

responsive to the signs of the peaks of the kernel and the frame being equal, multiplying the peak of the frame by minus one; and

adding the peak of the kernel to the samples to reduce the peak of the frame.

11. The method of claim 7 in a system in which more than one peak may be present per frame, comprising the steps of:

responsive to determining that a sample magnitude exceeds the predetermined threshold, applying the peak kernel to the sample, wherein the peak kernel applied for each sample has a magnitude scaled relative to an extent the sample magnitude exceeds the predetermined threshold.

12. The method of claim 11 wherein the scaling factors are chosen to ensure a sum of the magnitudes of the kernels applied is equal to one.